


PNP Silicon Epitaxial Planar Transistor

for high current application

SOT-89-3L



1. BASE
2. EMITTER
3. COLLECTOR



Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)






Parameter	Symbol	Value	Unit
Collector Base Voltage	$-V_{CB0}$	120	V
Collector Emitter Voltage	$-V_{CEO}$	120	V
Emitter Base Voltage	$-V_{EBO}$	5	V
Collector Current	$-I_C$	800	mA
Base Current	$-I_B$	160	mA
Total Power Dissipation	P_{tot}	0.5 1 ¹⁾	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

¹⁾ When mounted on a 250 mm² X 0.8 t ceramic substrate.

Characteristics at $T_a = 25^\circ\text{C}$


Parameter	Symbol	Min.	Typ.	Max.	Unit	
DC Current Gain at $-V_{CE} = 5\text{ V}$, $-I_C = 100\text{ mA}$	Current Gain Group O	h_{FE}	80	-	160	-
	Y	h_{FE}	120	-	240	-
Collector Base Cutoff Current at $-V_{CB} = 120\text{ V}$	$-I_{CB0}$	-	-	100	nA	
Emitter Base Cutoff Current at $-V_{EB} = 5\text{ V}$	$-I_{EBO}$	-	-	100	nA	
Collector Emitter Breakdown Voltage at $-I_C = 10\text{ mA}$	$-V_{(BR)CEO}$	120	-	-	V	
Emitter Base Breakdown Voltage at $-I_E = 1\text{ mA}$	$-V_{(BR)EBO}$	5	-	-	V	
Collector Emitter Saturation Voltage at $-I_C = 500\text{ mA}$, $-I_B = 50\text{ mA}$	$-V_{CE(sat)}$	-	-	1	V	
Base Emitter on Voltage at $-V_{CE} = 5\text{ V}$, $-I_C = 500\text{ mA}$	$-V_{BE(on)}$	-	-	1	V	
Transition Frequency at $-V_{CE} = 5\text{ V}$, $-I_C = 100\text{ mA}$	f_T	-	120	-	MHz	
Collector Output Capacitance at $-V_{CB} = 10\text{ V}$, $f = 1\text{ MHz}$	C_{ob}	-	-	30	pF	

Typical Characteristics




SOT-89-3L Tape and Reel

SOT-89-3L Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-89-3L	4.85	4.45	1.85	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOT-89-3L Tape Leader and Trailer




SOT-89-3L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø180.00	60.00	R32.00	R86.50	R30.00	Ø13.00	13.20	16.50

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
1000 pcs	7 inch	10,000 pcs	203×203×195	40,000 pcs	438×438×220	



SYMBOL	MILLIMETER		
	MIN	TYP.	MAX
A	1.400	1.500	1.600
b	0.320	0.400	0.520
b1	0.400	0.480	0.580
c	0.350	0.381	0.440
D	4.400	4.500	4.600
D1	1.700REF		
E	2.400	2.500	2.600
E1	4.050	4.200	4.350
e	1.500TYP.		
e1	3.000TYP.		
L	0.800	0.950	1.200
L1	0.700REF		
θ	10° REF		
$\theta 1$	8° REF		
$\theta 2$	10° REF		
$\theta 3$	5° REF		

DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.