


# SILICON EPITAXIAL PLANAR SCHOTTKY BARRIER DIODE

# PINNING

PIN	DESCRIPTION		
1	Cathode		
2	Anode		

for high speed switching circuit and small current rectification applications



Absolute Maximum Ratings (T<sub>a</sub> = 25 °C)

Parameter	Symbol	Value	Unit				
Reverse Voltage	$V_R$	30	V				
Average Forward Current	Io	200	mA				
Non-repetitve Peak Forward Surge Current	I <sub>FSM</sub>	1	Α				
Junction Temperature	T <sub>j</sub>	125	°C				
Storage Temperature Range	T <sub>stg</sub>	- 40 to + 125	°C				


#### Characteristics at T<sub>a</sub> = 25 °C


Parameter	Symbol	Max.	Unit
Forward Voltage at I <sub>F</sub> = 200 mA	V <sub>F</sub>	0.5	V
Reverse Current at V <sub>R</sub> = 10 V	I <sub>R</sub>	30	μΑ


0755-23619906 www.jhgsz.com Rev.01 1/4





#### **Typical Characteristics**












0755-23619906 www.jhgsz.com Rev.01 2 / 4





### SOD-523 Embossed Carrier Tape



Dimensions are in millimeter										
Pkg type	Α	В	С	d	Е	F	P0	Р	P1	W
SOD-523	0.9	1.94	0.73	Ø1.50	1.75	3.50	4.00	2.00	2.00	8.00

### SOD-523 Tape Leader and Trailer






Dimensions are in millimeter								
Reel Option	D	D1	D2	G	Н	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30


REEL	Reel Size	Вох	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
8000 pcs	7 inch	120,000 pcs	203×203×195	480,000 pcs	438×438×220	


0755-23619906 www.jhgsz.com Rev.01 3 / 4



#### **SOD-523 Package Outline Dimensions**







	MILLIMETER				
SYMBOL	MIN	MAX			
A	0. 530	0. 730			
A1	0. 500	0. 700			
b	0. 280	0. 380			
С	0. 080	0. 150			
D	0. 750	0.850			
Е	1. 100	1. 300			
E1	1. 500	1. 700			
E2	0. 200	) REF			
L	0. 010	0. 070			
θ	7° REF				

## **DISCLAIMER**

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for (1)selecting the appropriate JHG products for your application;

(2)designing, validating and testing your application;

(3)ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

0755-23619906 www.jhgsz.com Rev.01 4 / 4