


SILICON EPITAXIAL PLANAR SCHOTTKY BARRIER DIODE

Features

- Small surface mounting type
- Low reverse current
- Low forward voltage

MARKING: XM



Absolute Maximum Ratings (T_a = 25 °C)

Parameter	Symbol	Value	Unit	
Maximum Peak Reverse Voltage	V_{RM}	45	V	
Reverse Voltage	V_R	40	V	
Average Forward Current	Io	100	mA	
Maximum Peak Forward Current	I _{FM}	300	mA	
Power Disspation	P _D	150	mW	
Junction Temperature	T _j	125	°C	
Storage Temperature Range	T _{stg}	- 55 to + 125	°C	


Characteristics at T_a = 25 °C


Parameter	Symbol	Max.	Unit
Forward Voltage at I _F = 100 mA	V _F	0.6	V
Reverse Current at $V_R = 40 \text{ V}$	I _R	5	μA
Total Capacitance at $V_R = 0 \text{ V}$, $f = 1 \text{ MHz}$	Ст	25	pF


0755-23619906 www.jhgsz.com Rev.01 1/4



Typical Characteristics








0755-23619906 www.jhgsz.com Rev.01 2 / 4




SOT-23 Tape and Reel

SOT-23 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	Α	В	С	d	E	F	P0	Р	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer








Dimensions are in millimeter								
Reel Option D D1 D2 G H I W1 W2							W2	
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	

0755-23619906 www.jhgsz.com Rev.01 3 / 4



DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for (1)selecting the appropriate JHG products for your application;

(2)designing, validating and testing your application;

(3)ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

0755-23619906 www.jhgsz.com Rev.01 4 / 4