

- ★ Green Device Available
- ★ Super Low Gate Charge
- ★ Excellent Cdv/dt effect decline
- ★ Advanced high cell density Trench technology

## Product Summary




| BVDSS | RDSON | ID   |
|-------|-------|------|
| 100V  | 95 mΩ | 5.0A |

## Description

## SOT-23-3L Pin Configuration

The JHS1005 is the high cell density trenched N-ch MOSFETs, which provides excellent RDSON and efficiency for most of the small power switching and load switch applications.

The JHS1005 meet the RoHS and Green Product requirement with full function reliability approved.



## Absolute Maximum Ratings

| Symbol                 | Parameter                                  | Rating     | Units      |
|------------------------|--|------------|------------|
| $V_{DS}$               | Drain-Source Voltage                       | 100        | V          |
| $V_{GS}$               | Gate-Source Voltage                        | $\pm 20$   | V          |
| $I_D @ T_A=25^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V^1$ | 4.5        | A          |
| $I_D @ T_A=70^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V^1$ | 2.2        | A          |
| $I_{DM}$               | Pulsed Drain Current <sup>2</sup>          | 11         | A          |
| $P_D @ T_A=25^\circ C$ | Total Power Dissipation <sup>3</sup>       | 1          | W          |
| $T_{STG}$              | Storage Temperature Range                  | -55 to 150 | $^\circ C$ |
| $T_J$                  | Operating Junction Temperature Range       | -55 to 150 | $^\circ C$ |

## Thermal Data

| Symbol          | Parameter  | Typ. | Max. | Unit         |
|-----------------|--|------|------|--------------|
| $R_{\theta JA}$ | Thermal Resistance Junction-ambient <sup>1</sup> | ---  | 125  | $^\circ C/W$ |
| $R_{\theta JC}$ | Thermal Resistance Junction-Case <sup>1</sup>    | ---  | 80   | $^\circ C/W$ |

## Electrical Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise specified

| Symbol  | Parameter   | Test Condition  | Min. | Typ. | Max.      | Units      |
|---|---|---|------|------|-----------|------------|
| <b>Off Characteristic</b>                                     |   |   |      |      |           |            |
| $V_{(BR)DSS}$   | Drain-Source Breakdown Voltage  | $V_{GS} = 0V, I_D = 250\mu A$                               | 100  | 110  | -         | V          |
| $I_{DSS}$   | Zero Gate Voltage Drain Current   | $V_{DS} = 100V, V_{GS} = 0V$                                | -    | -    | 1         | $\mu A$    |
| $I_{GSS}$   | Gate to Body Leakage Current  | $V_{DS} = 0V, V_{GS} = \pm 20V$                             | -    | -    | $\pm 100$ | nA         |
| <b>On Characteristics</b> <sup>note3</sup>                    |   |   |      |      |           |            |
| $V_{GS(th)}$  | Gate Threshold Voltage  | $V_{DS} = V_{GS}, I_D = 250\mu A$                           | 1.0  | 1.95 | 3.0       | V          |
| $R_{DS(on)}$  | Static Drain-Source On-Resistance <sup>note2</sup>                        | $V_{GS} = 10V, I_D = 3A$                                    | -    | 95   | 140       | m $\Omega$ |
| <b>Dynamic Characteristics</b> <sup>note4</sup>               |   |   |      |      |           |            |
| $C_{iss}$   | Input Capacitance   | $V_{DS} = 50V, V_{GS} = 0V,$<br>$f = 1.0MHz$                | -    | 196  | -         | pF         |
| $C_{oss}$   | Output Capacitance  |   | -    | 25.9 | -         | pF         |
| $C_{rss}$   | Reverse Transfer Capacitance  |   | -    | 21.4 | -         | pF         |
| $Q_g$   | Total Gate Charge   | $V_{DS} = 50V, I_D = 3A,$<br>$V_{GS} = 10V$                 | -    | 4.3  | -         | nC         |
| $Q_{gs}$  | Gate-Source Charge  |   | -    | 3.5  | -         | nC         |
| $Q_{gd}$  | Gate-Drain("Miller") Charge   |   | -    | 3.1  | -         | nC         |
| <b>Switching Characteristics</b> <sup>note4</sup>             |   |   |      |      |           |            |
| $t_{d(on)}$   | Turn-On Delay Time  | $V_{DD} = 50V, I_{DS}=3A$<br>$R_G = 2\Omega, V_{GEN} = 10V$ | -    | 14.7 | -         | ns         |
| $t_r$   | Turn-On Rise Time   |   | -    | 3.5  | -         | ns         |
| $t_{d(off)}$  | Turn-Off Delay Time   |   | -    | 20.9 | -         | ns         |
| $t_f$   | Turn-Off Fall Time  |   | -    | 2.7  | -         | ns         |
| <b>Drain-Source Diode Characteristics and Maximum Ratings</b> |   |   |      |      |           |            |
| $I_S$   | Maximum Continuous Drain to Source Diode Forward Current <sup>note2</sup> |   | -    | -    | 4.5       | A          |
| $I_{SM}$  | Maximum Pulsed Drain to Source Diode Forward Current                      |   | -    | -    | 12        | A          |
| $V_{SD}$  | Drain to Source Diode Forward Voltage <sup>note3</sup>                    | $V_{GS} = 0V, I_S = 3A$                                     | -    | -    | 1.3       | V          |
| $t_{rr}$  | Body Diode Reverse Recovery Time  | $V_{GS} = 0V, I_F = 3A,$<br>$di/dt = 100A/\mu s$            | -    | 32.1 | -         | ns         |
| $Q_{rr}$  | Body Diode Reverse Recovery Time Charge                                   |   | -    | 39.4 | -         | nC         |
| $I_{rrm}$   | Peak Reverse Recovery Current   |   | -    | 2.1  | -         | A          |

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board,  $t \leq 10$  sec.
3. Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$ .
4. Guaranteed by design, not subject to production
5.  $V_{DD}=50$  V,  $R_G=50$   $\Omega$ ,  $L=0.3$  mH, starting  $T_j=25$   $^{\circ}\text{C}$

## Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Forward Characteristics of Reverse




Figure 4.  $R_{DS(ON)}$  vs.  $V_{GS}$




Figure 5.  $R_{DS(ON)}$  vs.  $I_D$







Figure 6. Normalized  $R_{DS(ON)}$  vs. Temperature




## SOT-23-3L Tape and Reel

### SOT-23-3L Embossed Carrier Tape




| Dimensions are in millimeter |      |      |      |       |      |      |      |      |      |      |
|------------------------------|------|------|------|-------|------|------|------|------|------|------|
| Pkg type                     | A    | B    | C    | d     | E    | F    | P0   | P    | P1   | W    |
| SOT-23                       | 3.15 | 2.77 | 1.22 | Ø1.50 | 1.75 | 3.50 | 4.00 | 4.00 | 2.00 | 8.00 |

### SOT-23-3L Tape Leader and Trailer




### SOT-23-3L Reel



| Dimensions are in millimeter |         |       |       |        |        |       |      |       |
|------------------------------|---------|-------|-------|--------|--------|-------|------|-------|
| Reel Option                  | D       | D1    | D2    | G      | H      | I     | W1   | W2    |
| 7" Dia                       | Ø178.00 | 54.40 | 13.00 | R78.00 | R25.60 | R6.50 | 9.50 | 12.30 |

| REEL     | Reel Size | Box        | Box Size(mm) | Carton      | Carton Size(mm) | G.W.(kg) |
|----------|-----------|------------|--------------|-------------|-----------------|----------|
| 3000 pcs | 7 inch    | 45,000 pcs | 203×203×195  | 180,000 pcs | 438×438×220     |          |



| SYMBOL   | MILLIMETER |       |
|----------|------------|-------|
|          | MIN        | MAX   |
| A        | 0.900      | 1.150 |
| A1       | 0.000      | 0.100 |
| A2       | 0.900      | 1.050 |
| b        | 0.300      | 0.500 |
| c        | 0.080      | 0.150 |
| D        | 2.800      | 3.000 |
| E        | 1.200      | 1.400 |
| E1       | 2.250      | 2.550 |
| e        | 0.950 TYP  |       |
| e1       | 1.800      | 2.000 |
| L        | 0.550 REF  |       |
| L1       | 0.300      | 0.500 |
| $\theta$ | 0°         | 8°    |

## DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.